

**1635-S**
**Closed end connector terminals, for free connections**

Insulating housing: transparent polycarbonate UL94 V0  
Conductive body: brass  
Captive screw: galvanized steel  
Self-extinguishing: EN60695-2-10 a 850°C, EN 60335-1:2002 +A2:2006, EN60695-2-11  
Working temperature: max. 85 °C  
Degree of protection: IP20  
Reference standards: EN60998-1: EN60998-2-1:2004



|  | art.   | mm² | mm² | L<br>mm | L1<br>mm | S<br>mm | N |
|---------------------------------------------------------------------------------|--------|-----|-----|---------|----------|---------|---|
| <b>BM991</b>                                                                    | BM991  | 1.5 | 1.5 | 15      | 7.5      | 14.5    | 2 |
| <b>BM992</b>                                                                    | BM992  | 2.5 | 2.5 | 17.5    | 9        | 18.2    | 2 |
| <b>BM9924</b>                                                                   | BM9924 | 4   | 4   | 21      | 10.3     | 20      | 2 |
| <b>BM993</b>                                                                    | BM993  | 6   | 6   | 22.5    | 11.8     | 23      | 2 |
| <b>BM994</b>                                                                    | BM994  | 10  | 10  | 26      | 14.7     | 26      | 2 |
| <b>BM995</b>                                                                    | BM995  | 16  | 16  | 31.8    | 18.8     | 32.2    | 2 |
| <b>BM9960</b>                                                                   | BM9960 | 25  | 25  | 36.3    | 22.5     | 41.9    | 2 |
| <b>BM9961</b>                                                                   | BM9961 | 35  | 35  | 43.5    | 26.1     | 49.4    | 2 |